

TARGET MARKETS



OIL & GAS [Upstream]



Black Eagle Snap Tite

3-5 times Widest Range longer service (1/8"~ 6"), life materials: SS316, -HastelloyC276, Inconel



Snap TiteF37Widest RangeEco-friendly

"), **NON Welding** S316, Solution



PEACH Gemini I Purasep

Filter separator and coalescer in one **continuous** element.



emini Parmax-R

High flowrates with compact footprint. Low capital and operating cost. Robust cage design.



Autoclave

AES222 tubing Eas standard wit Compliance turn. Widest Pressure f & Size ranges id (150,000 Psi – (moly OD up to 1 ½")



MPI[™] Fittings Accumulator

Easiest to install with only **1-1/2** turn. Safest fittings from visual identification (**molybdenum** male nut)



Deep Sea Pressure compensator allowing design pressure reduction driving cost

down





Filter separator and coalescer in **one continuous** element.



STA CASE IN AN AN AN AN ANALY MANY AND SAME THAT

Parmax-R

Highest flowrates with compact footprint. Low capital and operating cost. Robust cage design.



Integral A-Lok

Removes NPT, eliminates thread galling, negates the need for sealant or thread tape and prevents the opportunity for stress cracking.



Ball Valves

SIL 2 Rating for ESD and Safety Critical Applications



MAC/ATEX Cooler

ATEX compliant, cooling capacity up to 300 kW, MAC meets corrosion resistance C4M & C5M-M according to ISO 12944.





Norsok / API Compliance O-Rings

FFKM, FKF, HNBR, EPDM designed for Oil and Gas applications. Added new products like Flexi joints and Gimbal bearings for off-shore production



EPS Seal

Polypak, Wiper Seal, Piston Seal, T-seals made of different material. These metal seals withstand high temperature and high pressure applications



PEACH Gemini Parmax-R Purasep

Filter separator and coalescer in one continuous element. High flowrates with compact footprint. Low capital and operating cost. Robust cage design.

63





Metal Hose

Larger OD up to 12", Higher extreme temperatures (-228°C ~ +648 °C),



Titan Purasep

Safer, hassle free changeout. Reduce changeout time by 85%



PEACH Gemini Purasep

Filter separator and coalescer in one continuous element.



Parmax-R

with compact

footprint. Low

capital and

Robust cage

design.

Gas Turbine Filters

High flowrates OE filters manufacturer for gas turbine world market operating cost. leader **GE** of 60% market share



material.

A-Lok Fittings

Manifold

Parker CPI[™] / A-Ready approved LOK® Ferrule under design with TAMAP 2 went ASTM G48 stars corrosion test. Available in 6 Mo and NORSOK M650



SEMICONDUCTOR [Micro Electronics]



FFKM O-rings

PSG 5020, CSS 5115 Competitive price and design abilities for long life span usage bonded slit valve and cost savings doors any



Slit Valve Doors

Fittina globally Extreme

referenced by temperature up semicon market to 260°c. available in Inch & Metric, comes in 9 different colors



801 Hose and PFA Tubing Domnick Hunter **Oil-X Filters**

> Lowest total cost of ownership on the market via saturated pressure drop of 125mbar



Veriflo diaphragm Ventrean material exceeding F22 5 million cycles life time for WF6.

Superior Diaphragm reliability with HC-22 as standard diaphragm material. Vericlean material exceeding SEMI F20.

Veriflo regulators



Electromechanica

Origa Cylinder

Rodless, metal to metal seal gives high speed/temperature with low wear. Slow speed grease. Long life - 8 million meters

Positioning System "Perfect Fit" solutions covering a broad spectrum of requirements at various levels of integration and complexity

custom make seals

PSG 5020, CSS

5115

One stop

solution for

rubber and





471TC Hose 1/2" Bend Radius TC Cover(80 times) US Army referenced



EO Fitting Cu Ni Fe suitable for sea water, Marine certified



Racor Diesel Filters

Engines will benefit from near 100% water separation and fuel filtration with Racor's proprietary Aquabloc® water repelling media



rs Baldwin Filters

Proven better OE filters performance and long service life



F11/12 Fixed Displacement Motor Compact, robust and

reliable motor, high speed capability up to 10,000 rpm, high efficiency and wide range meets customer needs



[Pharmaceutical]



Parker O-Ring

ORD 5712 NSF, UL,USP Class VI, FDA and many rubber compound including FFKM compound. Kanban and JIT service to support local OEMs



PFA Tubing

Operates up to 260°c, Available in Inch & Metric, comes in 9 different colors, FDA Approved



PVC Hose

OD Up to 8" FDA Approved



High Flow Tetpor II

An extremely robust sterile gas filter validated for 225 steam sterilization cycles



Sensors

Highly accurate flow through single use pressure, conductivity and temperature sensors







PFA Tubing

Operates up to 260°c, Available in Inch & Metric, comes in 9 different colors, FDA Approved

68



PVC Hose

OD Up to 8"

FDA Approved

Sterilizing gas filter, validated to withstand over 100 reverse steam sterilization cycles without the need for condensation management

Asept X



High Flow Bio-X

Sterile gas filter with exceptionally high flow rate and low pressure drop that enables dramatically reduced installation size



Bevpor BR

Offers maximized service life and ensure microbial stability during cold stabilization of beer



Filter Dryer

It's the CORE that counts! Specially formulated core with molecular sieve and activated alumina for exceptional moisture / acid removal in one pass



Zoomlock Fittings

Flame-Free Refrigerant Fittings! Makes job simpler and faster when joining copper tubes.

No hot work permits required. No need to nitrogen-purge. Gives a clean system.

MINING [Equipment]



MSHA Approved Hoşę_sand Fitting



Racor Diesel Filters Balo

Leader in global diesel filtration applications with proven 98% fuel water separation Aqua Block III patented media



rs Baldwin Filters

Offer Heavy Duty/ Severe Service filters to give extra protection to your equipment operating in harsh environment



Multiple Motion

configuration suitable for

customized solution with

IOAN control. Sectional

design allows great

flexibility of machine

design.

L90LS mobile valve Electronic

Control System

IQAN controller, Complete freedom to design customized software without the need for advanced programming skill.





MSHA Approved Hosenand Fitting



Clean Diesel

Filtration & Fuel Condition Monitoring Solutions offering particulate, coalescing, water absorbent media to meet all different diesel requirement



Nitrogen Generator

Improved safety and minimized flammability concerns through Parker N2 membrane system.



Gold Cup Pump

Hydrostatic P&M, Robust Design with superior longlasting performance in severe duty applications. Fast and stable control.





Global Core Hose & Fitting EO

Simplified with only 5 hoses and 2 series fitting, Marine Certified

ZABS



EO Fitting

MSHA

Cu Ni Fe suitable for sea water, Marine



Racor Marine Filters Baldwin Filters

Leader in global diesel filtration applications with proven 98% fuel water separation Aqua Block III patented media. With approved class certification for Marine requirement. Offer Heavy Duty/ Severe Service filters to give extra protection to your equipment operating in harsh environment



PV Pumps Heavy duty (350bar). Compact design, low noise level, fewer flowand pressure pulsations than conventional pumps. Modular Design and service friendly



CVG Control Valve

Excellent controllability up to **2,000 l/min**. Flexible, modular design load sensing valve with pressure compensation and low hysteresis and ease of service







Metal Hose

Larger OD up to **12**", Higher extreme temperatures (-228°C ~ +648 °C),




Parmax-R

High flowrates with compact footprint. Low capital and operating cost. Robust cage design.



Gas Turbine Filters OE filters manufacturer for gas turbine world market leader GE of 60% market share



Significant installed base in the region with proven Parker's purifier solutions protecting vital components



Needle Valve

Parker U Series Union with **649 Deg C** operating temperature



Hydraulic Power Unit

Wide Parker products coverage, quieter operation, elimination of potential leak point, maintains trouble-free performance

72

CONSTRUCTION



Global Core Hose & Fitting

Simplified with only 5 hoses and 2 series fitting, PTS



Racor Diesel Filters

Engines will benefit from near 100% water separation and fuel filtration with Racor's proprietary Aquabloc® water repelling media



Baldwin Filters

Offer Heavy Duty/ Severe Service filters to give extra protection to your equipment operating in harsh environment



MO200/300EX MCV

5% Fuel savings from larger spool size & stroke



P2/P3 Mobile Pumps

High Self Priming Speed,

Low noise, High altitude

operation capability due

to built in impeller

design

97 2 97

F11/12 Fixed Displacement Motor

Compact, robust and reliable motor, high speed capability **up to 10,000 rpm**, high efficiency and wide range meets customer needs

73

BUS & TRUCK



Air Brake Tubing Air Brake Fitting

Global references, Less downtime due to **kinking** failure Global references, Push To Connect



Racor Diesel Filters

Engines will benefit from near 100% water separation and fuel filtration with Racor's proprietary Aquabloc® water repelling media



Baldwin Filters

Offer Heavy Duty/ Long Service Life filters to give extra protection to your equipment operating in harsh environment



Solenoid valve – 7V

7 Coils, compatible with all CFC, HCFC and HFC refrigerants and blends and most refrigeration oils. Fully compliant to 97/23/CE (PED), 2006/95/CE (Low Voltage), RoHS.

STEEL MILL



Metal Hose

Larger OD up to 12", **Higher** extreme temperatures (-228°C ~ +648 °C),

75



BHA Bag Filters

ePTFE Membrane Laminated Filter Bags for Air Pollution Control with better PM2.5 filtration performance



Parker Hydraulic Filters

Quantumfiber media with extended element life. improved efficiency and 10% lower pressure drop



Isomax Valve

Ceramic Technology. Long life>100 million operations. Low sensitivity to air quality changes: switching without seal. Stiction free. Slide valve: high flow/size ratio. Low friction switching : minimum wear



"Jewel" Rod Gland Assembly-Externally removable without cylinder disassembly. Long bearing surface is inboard of the seals assuring positive lubrication from within the cylinder



Pneumatic Cylinder Hydraulic Power Unit Hydraulic Cylinder

Wide Parker products coverage, quieter operation, elimination of potential leak points, maintains a trouble-free performance

Compact design for tough operation and long service life. Easy to service using standard tools. Choice of material, mounting, seals and surface treatment





15

ORD 5712 NSF, UL, USP Class VI, FDA, Military, Aerospace and many rubber compounds available for selection. Kanban and JIT service to support local OEMs



BHA Bag

Filters

ePTFE

Membrane

Laminated

Filter Bags for

Air Pollution

Control

Parmax-R High flowrates with compact footprint. Low capital and operating cost. Robust cage design.



Hydraulic Filters Quantumfiber media with extended element life, improved efficiency, 10% lower pressure drop



Isomax Valve

Ceramic Technology.

Long life>100 million

cycles. switching without

seal. Stiction free. Slide

valve: high flow/size

ratio. Low friction

switching: minimum

wear

SP?

Pneu/Hyd Cylinder

"Jewel" Rod Gland Assembly-Externally removable without cylinder disassembly.

THIS IS PARKER

ENGINEERING YOUR SUCCESS



